SAMSUNG

Samsung Electronics Co., Ltd.

Samsung Electronics Co., Ltd. inspires the world and shapes the future with transformative ideas and technologies. The company is redefining the worlds of TVs, smartphones, wearable devices, tablets, cameras, digital appliances, medical equipment, network systems, and semiconductor and LED solutions. For the latest news, please visit the Samsung Newsroom at news.samsung.com.

Samsung Display Solutions

For more information about Samsung display solutions, visit
www.samsung.com/business or www.samsung.com/displaysolutions

Copyright © 2020 Samsung Electronics Co. Ltd. All rights reserved. Samsung is a registered trademark of Samsung Electronics Co. Ltd. Specifications and designs are subject to change without notice. Non-metric weights and measurements are approximate. All data were deemed correct at time of creation. Samsung is not liable for errors or omissions. All brand, product, service names and logos are trademarks and/or registered trademarks of their respective owners and are hereby recognized and acknowledged.

www.samsung.com/tw/ | **0809-00-5237**

*本型錄僅供參考，產品以實際規格為主。

SAMSUNG
商用顯示器

SAMSUNG DISPLAY SOLUTIONS

UHD

是時候升級你的顯示器

特色

UHD 解析度

擁有4K高畫質解析度，更清晰呈現栩栩如生的畫面。

UHD 智慧影像升頻技術

能將低解析度內容升頻為UHD等級畫質。

純晶透顯色技術

呈現更廣大的色譜—高達10億種不同色調，捕捉色彩細微差異，帶來完美的色彩表現。

內嵌媒體播放器

一體成型的解決方案無須任何外接裝置，簡化安裝與維護過程。

纖薄對稱設計

採用全新的對稱設計，簡化牆面安裝，使機身與牆面達到零縫隙。

旋轉功能

支援橫向與縱向模式，提供更大的靈活度。

防眩光螢幕

無論室內的光線狀況為何，都能確保提供更清晰的畫面。

內建 Wi-Fi

帶來更個人化與互動式的服務，使螢幕呈現更便捷。

*部分功能可能因機種不同而有所差異。

規格表

型 號			QH43R	QH50R	QH55R	QH65R	QH75R
面 板	對角線尺寸		43	50	55	65	75
	解析度		3840 x 2160	3840 x 2160	3840 x 2160	3840 x 2160	3840 x 2160
	亮度(典型值)		700	700	700	700	700
	對比度		4000:1	4000:1	4000:1	4000:1	4000:1
	可視角度(水平/垂直)		178/178	178/178	178/178	178/178	178/178
	反應時間		8ms(Typ.)	8ms(Typ.)	8ms(Typ.)	8ms(Typ.)	8ms(Typ.)
	使用小時		24/7	24/7	24/7	24/7	24/7
	霧度Haze(%)		44%	25%	25%	25%	44%
聲 音	喇叭類型		Built in Speaker(10W+10W)	Built in Speaker(10W+10W)	Built in Speaker(10W+10W)	Built in Speaker(10W+10W)	Built in Speaker(10W+10W)
連結性	輸 入	RGB	DVI-D,Display Port1.2(1)	DVI-D,Display Port1.2(1)	DVI-D,Display Port1.2(1)	DVI-D,Display Port1.2(1)	DVI-D,Display Port1.2(1)
		VIDEO	HDMI 2.0 (2)	HDMI 2.0 (2)	HDMI 2.0 (2)	HDMI 2.0 (2)	HDMI 2.0 (2)
		HDCP	HDCP2.2	HDCP2.2	HDCP2.2	HDCP2.2	HDCP2.2
		AUDIO	Stereo mini Jack, DVI, HDMI	Stereo mini Jack, DVI, HDMI	Stereo mini Jack, DVI, HDMI	Stereo mini Jack, DVI, HDMI	Stereo mini Jack, DVI, HDMI
		USB	USB 2.0 x 2	USB 2.0 x 2	USB 2.0 x 2	USB 2.0 x 2	USB 2.0 x 2
	輸 出	RGB	HDMI 2.0 (Loop-out)	HDMI 2.0 (Loop-out)	HDMI 2.0 (Loop-out)	HDMI 2.0 (Loop-out)	HDMI 2.0 (Loop-out)
		VIDEO	N/A	N/A	N/A	N/A	N/A
		AUDIO	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack
	外部控制		RS232C(in/out) thru stereo jack, RJ45	RS232C(in/out) thru stereo jack, RJ45	RS232C(in/out) thru stereo jack, RJ45	RS232C(in/out) thru stereo jack, RJ45	RS232C(in/out) thru stereo jack, RJ45
	外部感測器		IR	IR	IR	IR	IR
電 源	電源供應		AC100 - 240 V~ (+/-10 %), 50/60 Hz	AC100 - 240 V~ (+/-10 %), 50/60 Hz	AC100 - 240 V~ (+/-10 %), 50/60 Hz	AC100 - 240 V~ (+/-10 %), 50/60 Hz	AC100 - 240 V~ (+/-10 %), 50/60 Hz
	耗電量	最大值	138	N/A	160	204	314
		平均值	96	N/A	118	150	247
		睡眠模式	0.5	0.5	0.5	0.5	0.5
機械規格	機身尺寸(mm)		967.5 x 557.7 x 48.3	1121.4 x 643.9 x 46.3	1235.1 x 707.9 x 46.3	1453.9x 831.0 x 46.3	1681.1 x 960.1 x 49.7
	機身重量(kg)		10	13.4	18.1	24.9	38.3
	VESA 壁掛		200 X 200	200 X 200	200 X 200	400 X 400	400 X 400
	邊框寬度 (mm)		9.2 (U/L/R),11.2(B)	9.2 (U/L/R),11.2(B)	9.2 (U/L/R),11.2(B)	9.2 (U/L/R),11.2(B)	11.5 (U/L/R),12.5(B)
操 作	操作溫度/濕度		0℃~40℃ / 10~80%	0℃~40℃ / 10~80%	0℃~40℃ / 10~80%	0℃~40℃ / 10~80%	0℃~40℃ / 10~80%
特殊功能	硬 體		Temperature Sensor, Pivot Display, Clock Battery(168hrs Clock Keeping), Built in Speake(10W2ch) , Video Wall Daisy Chain(HDCP2.2:4EA,HDCP 1.4:7EA),IP5x Rating,Wi-Fi/BT				
	軟 體		Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option, Plug&Play (Initial Setting), 802. 1x(WPA2 Enterprise) Certified				
內部媒體播放器	嵌入式		Yes	Yes	Yes	Yes	Yes
	作業系統		Tizen 4.0 (VDLinux)	Tizen 4.0 (VDLinux)	Tizen 4.0 (VDLinux)	Tizen 4.0 (VDLinux)	Tizen 4.0 (VDLinux)
	SSSP		MagicInfo S6, SSSP 6.0	MagicInfo S6, SSSP 6.0	MagicInfo S6, SSSP 6.0	MagicInfo S6, SSSP 6.0	MagicInfo S6, SSSP 6.0

規格表

型 號			QM32R	QM43R	QM50R	QM55R	QM65R	QM75R	QM85R
面 板	對角線尺寸		32	43	50	55	65	75	85
	解析度		1920 x 1080	3840 x 2160	3840 x 2160	3840 x 2160	3840 x 2160	3840 x 2160	3840 x 2160
	亮度(典型值)		400	500	500	500	500	500	500
	對比度		5000:1	4000:1	4000:1	4000:1	4000:1	4000:1	4000:1
	可視角度(水平/垂直)		178/178	178/178	178/178	178/178	178/178	178/178	178/178
	反應時間		8ms(Typ.)	8ms(Typ.)	8ms(Typ.)	8ms(Typ.)	8ms(Typ.)	8ms(Typ.)	8ms(Typ.)
	使用小時		24/7	24/7	24/7	24/7	24/7	24/7	24/7
	霧度Haze(%)		2%	44%	25%	25%	25%	44%	25%
聲 音	喇叭類型		Built in Speaker(10W+10W)	Built in Speaker(10W+10W)	Built in Speaker(10W+10W)	Built in Speaker(10W+10W)	Built in Speaker(10W+10W)	Built in Speaker(10W+10W)	Built in Speaker(10W+10W)
連結性	輸 入	RGB	Display Port1.2(1)	DVI-D,Display Port1.2(1)	DVI-D,Display Port1.2(1)	DVI-D,Display Port1.2(1)	DVI-D,Display Port1.2(1)	DVI-D,Display Port1.2(1)	DVI-D,Display Port1.2(1)
		VIDEO	HDMI 2.0 (1)	HDMI 2.0 (1)	HDMI 2.0 (2)	HDMI 2.0 (2)	HDMI 2.0 (2)	HDMI 2.0 (2)	HDMI 2.0 (2)
		HDCP	HDCP2.2	HDCP2.2	HDCP2.2	HDCP2.2	HDCP2.2	HDCP2.2	HDCP2.2
		AUDIO	Stereo mini Jack, HDMI	Stereo mini Jack, DVI, HDMI	Stereo mini Jack, DVI, HDMI	Stereo mini Jack, DVI, HDMI	Stereo mini Jack, DVI, HDMI	Stereo mini Jack, DVI, HDMI	Stereo mini Jack, DVI, HDMI
		USB	USB 2.0 x 2	USB 2.0 x 2	USB 2.0 x 2	USB 2.0 x 2	USB 2.0 x 2	USB 2.0 x 2	USB 2.0 x 2
	輸 出	RGB	HDMI 2.0 (Loop-out)	HDMI 2.0 (Loop-out)	HDMI 2.0 (Loop-out)	HDMI 2.0 (Loop-out)	HDMI 2.0 (Loop-out)	HDMI 2.0 (Loop-out)	HDMI 2.0 (Loop-out)
		VIDEO	N/A	N/A	N/A	N/A	N/A	N/A	N/A
		AUDIO	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack
	外部控制		RS232C(in/out) thru stereo jack, RJ45	RS232C(in/out) thru stereo jack, RJ45	RS232C(in/out) thru stereo jack, RJ45	RS232C(in/out) thru stereo jack, RJ45	RS232C(in/out) thru stereo jack, RJ45	RS232C(in/out) thru stereo jack, RJ45	RS232C(in/out) thru stereo jack, RJ45
	外部感測器		IR	IR	IR	IR	IR	IR	IR
電 源	電源供應		AC 100 - 240 V~ (+/- 10 %), 50/60 Hz	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz
	耗電量	最大值	72	110	170.5	143	181.5	231	308
		平均值	44	74	117	108	131	178	217
		睡眠模式	0.5	0.5	0.5	0.5	0.5	0.5	0.5
機械規格	機身尺寸(mm)		725.1 x 419.6 x 34.6	967.5 x 557.7 x 48.3	1121.4 x 643.9 x 46.3	1235.1 x 707.9 x 46.3	1453.9 x 831.0 x 46.3	1681.1 x 960.1 x 49.7	1897.8 x 1080.8 x 56.7
	機身重量(kg)		5.7	10	13.4	18.1	24.9	38.3	48.4
	VESA 壁掛		200 X 200	200 X 200	200 X 200	200 X 200	400 X 400	400 X 400	600 X 400
	邊框寬度 (mm)		8.8 (U/L/R/B)	9.2 (U/L/R),11.2(B)	9.2 (U/L/R),11.2(B)	9.2 (U/L/R),11.2(B)	9.2 (U/L/R),11.2(B)	11.5(U/L/R),12.5(B)	10.9 (U/L/R),12.9(B)
操 作	操作溫度/濕度		0℃~40℃ / 10~80%	0℃~40℃ / 10~80%	0℃~40℃ / 10~80%	0℃~40℃ / 10~80%	0℃~40℃ / 10~80%	0℃~40℃ / 10~80%	0℃~40℃ / 10~80%
特殊功能	硬 體		Temperature Sensor, Pivot Display, Clock Battery(168hrs Clock Keeping), Built in Speaker(10W 2ch), Video Wall Daisy Chain(HDCP2.2:4EA,HDCP1.4:7EA),IP5x Rating, Wi-Fi/BT						Temperature Sensor, Pivot Display, Clock Battery(168hrs Clock Keeping), Built in Speaker(10W 2ch),Video Wall Daisy Chain (HDCP2.2:4EA,HDCP1.4:7EA), Wi-Fi/BT
	軟 體		Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option, Plug&Play (Initial Setting)						Auto Source Switching & Recovery, LFD Home UI,Button Lock,Hot key option, Plug&Play(Initial Setting),SSSP 6.0a (MPAS Enterprise) Certified
內部媒體播放器	嵌入式		Yes	Yes	Yes	Yes	Yes	Yes	Yes
	作業系統		Tizen 4.0 (VDLinux)	Tizen 4.0 (VDLinux)	Tizen 4.0 (VDLinux)	Tizen 4.0 (VDLinux)	Tizen 4.0 (VDLinux)	Tizen 4.0 (VDLinux)	Tizen 4.0 (VDLinux)
	SSSP		MagicInfo S6, SSSP 6.0	MagicInfo S6, SSSP 6.0	MagicInfo S6, SSSP 6.0	MagicInfo S6, SSSP 6.0	MagicInfo S6, SSSP 6.0	MagicInfo S6, SSSP 6.0	MagicInfo S6, SSSP 6.0

規格表

型 號			QM98T	QB43R	QB50R	QB55R	QB65R	QB75R	QB85R	QB98T
面 板	對角線尺寸		98	43	50	55	65	75	85	98
	解析度		3840 x 2160	3840 x 2160	3840 x 2160	3840 x 2160	3840 x 2160	3840 x 2160	3840 x 2160	3840 x 2160
	亮度(典型值)		500	350	350	350	350	350	350	350
	對比度		4000:1	4000:1	4000:1	4000:1	4000:1	4000:1	4000:1	4000:1
	可視角度(水平/垂直)		178/178	178/178	178/178	178/178	178/178	178/178	178/178	178/178
	反應時間		8ms(Typ.)	8ms(Typ.)	8ms(Typ.)	8ms(Typ.)	8ms(Typ.)	8ms(Typ.)	8ms(Typ.)	8ms(Typ.)
	使用小時		24/7	16/7	16/7	16/7	16/7	16/7	16/7	24/7
	霧度Haze(%)		25%	2%	2%	2%	2%	2%	2%	25%
聲 音	喇叭類型		Built in Speaker(10W+10W)	Built in Speaker(10W+10W)	Built in Speaker(10W+10W)	Built in Speaker(10W+10W)	Built in Speaker(10W+10W)	Built in Speaker(10W+10W)	Built in Speaker(10W+10W)	Built in Speaker(10W+10W)
連結性	輸 入	RGB	DVI-D,Display Port1.2(1)	DVI-D	DVI-D	DVI-D	DVI-D	DVI-D	DVI-D	DVI-D,Display Port1.2(1)
		VIDEO	HDMI 2.0 (1)	HDMI 2.0 (2)	HDMI 2.0 (2)	HDMI 2.0 (2)	HDMI 2.0 (2)	HDMI 2.0 (2)	HDMI 2.0 (2)	HDMI 2.0 (2)
		HDCP	HDCP2.2	HDCP2.2	HDCP2.2	HDCP2.2	HDCP2.2	HDCP2.2	HDCP2.2	HDCP2.2
		AUDIO	Stereo mini Jack, DVI, HDMI	Stereo mini Jack, DVI, HDMI/Audio(Common)	Stereo mini Jack, DVI, HDMI	Stereo mini Jack, DVI, HDMI/Audio(Common)	Stereo mini Jack, DVI, HDMI/Audio(Common)	Stereo mini Jack, DVI, HDMI/Audio(Common)	Stereo mini Jack, DVI, HDMI	Stereo mini Jack, DVI, HDMI
		USB	USB 2.0 x 2	USB 2.0 x 2	USB 2.0 x 2	USB 2.0 x 2	USB 2.0 x 2	USB 2.0 x 2	USB 2.0 x 2	USB 2.0 x 2
	輸 出	RGB	HDMI 2.0 (Loop-out)	N/A	N/A	N/A	N/A	N/A	N/A	HDMI 2.0 (Loop-out)
		VIDEO	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
		AUDIO	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack
	外部控制		RS232C(in/out) thru stereo jack, RJ45	RS232C(in/out) thru stereo jack, RJ45	RS232C(in/out) thru stereo jack, RJ45	RS232C(in/out) thru stereo jack, RJ45	RS232C(in/out) thru stereo jack, RJ45	RS232C(in/out) thru stereo jack, RJ45	RS232C(in/out) thru stereo jack, RJ45	RS232C(in/out) thru stereo jack, RJ45
	外部感測器		IR	IR	IR	IR	IR	IR	IR	IR
電 源	電源供應		AC 100 - 240 V~ (+/- 10 %), 50/60 Hz	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz
	耗電量	最大值	528	110	143	143	181.5	231	198	528
		平均值	372	67	86	108	128	150	143	372
		睡眠模式	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5
機械規格	機身尺寸(mm)		2194.2 x 1250.2 x 96.2	967.5 x 557.7 x 48.3	1121.4 x 643.9 x 46.3	1235.1 x 707.9 x 46.3	1453.9 x 831.0 x 46.3	1681.1 x 960.1 x 49.7	1897.8x 1080.8x 56.7	2194.2x 1250.2x 96.2
	機身重量(kg)		–	10	13.4	18.1	24.9	38.3	48.4	–
	VESA 壁掛		800 X 400	200 X 200	200 X 200	200 X 200	400 X 400	400 X 400	600 X 400	800 X 400
	邊框寬度 (mm)		–	9.2 (U/L/R),11.2(B)	9.2 (U/L/R),11.2(B)	9.2 (U/L/R),11.2(B)	9.2 (U/L/R),11.2(B)	11.5 (U/L/R),12.5(B)	10.9 (U/L/R),12.9(B)	–
操 作	操作溫度/濕度		0℃~40℃ / 10~80%	0℃~40℃ / 10~80%	0℃~40℃ / 10~80%	0℃~40℃ / 10~80%	0℃~40℃ / 10~80%	0℃~40℃ / 10~80%	0℃~40℃ / 10~80%	0℃~40℃ / 10~80%
特殊功能	硬 體		Temperature Sensor,Pivot Display, Clock Battery(168hrs Clock Keeping), Built in Speaker(10W 2ch),Video Wall Daisy Chain (HDCP2.2:4EA,HDCP1.4:7EA), Wi-Fi/BT	Temperature Sensor, Pivot Display, Clock Battery(168hrs Clock Keeping), Built in Speaker(10W 2ch), IP5x Rating, Wi-Fi/BT						
	軟 體		Auto Source Switching & Recovery, LFD Home UI,Button Lock,Hot key option, Plug&Play(Initial Setting),SSSP 6.0a (MPAS Enterprise) Certified	Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option, Plug&Play (Initial Setting)						
內部媒體播放器	嵌入式		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
	作業系統		Tizen 4.0 (VDLinux)	Tizen 4.0 (VDLinux)	Tizen 4.0 (VDLinux)	Tizen 4.0 (VDLinux)	Tizen 4.0 (VDLinux)	Tizen 4.0 (VDLinux)	Tizen 4.0 (VDLinux)	Tizen 4.0 (VDLinux)
	SSSP		MagicInfo S6, SSSP 6.0	MagicInfo S6, SSSP 6.0	MagicInfo S6, SSSP 6.0	MagicInfo S6, SSSP 6.0	MagicInfo S6, SSSP 6.0	MagicInfo S6, SSSP 6.0	MagicInfo S6, SSSP 6.0	MagicInfo S6, SSSP 6.0

01 LCD Signage

長條型顯示器

有效地充分利用空間

SHR 系列

特色

特殊超寬比例 (16:4.5)
提供狹小空間內有效傳播訊息的能力。

700 nit亮度
以最佳亮度提供吸睛內容，且不會干擾人流。

防眩光螢幕
無論室內的光線狀況為何，都能確保提供更清晰的畫面。

24/7不間斷運作
可24小時不間斷運作，使訊息內容提供更持久。

內嵌媒體播放器
無須任何外接媒體播放器，便能有效、無縫地播放內容。

纖薄設計
厚度僅44.8mm的纖薄體積，能運用更多空間。

菊鍊UHD
利用HDMI Loop輸出與USB播放，輕鬆顯示與管理UHD內容。

旋轉功能
支援橫向與縱向模式，提供更大的靈活度。

規格表

型　號			SH37R
面 板	對角線尺寸		37
	解析度		1920x540
	亮度(典型值)		700nit
	對比度		4000:1
	可視角度(水平/垂直)		178:178
	反應時間		6.5ms
	使用小時		24/7
	霧度Haze(%)		28%
聲 音	喇叭類型		N/A
連結性	輸 入	RGB	Display Port 1.2
		VIDEO	HDMI 2.0 (2)
		HDCP	HDCP 2.2
		AUDIO	N/A
		USB	USB 2.0 x 1
	輸 出	RGB	HDMI 2.0 (1)
		VIDEO	N/A
		AUDIO	Stereo mini Jack
	外部控制		RS232C(in/out), RJ45
	外部感測器		IR
電 源	電源供應		AC100 - 240 V~ (+/- 10 %), 50/60 Hz
	耗電量	最大值	70
		平均值	52
		睡眠模式	less than 0.5W
機械規格	機身尺寸(mm)		923.3 X 2776 X 44.8
	機身重量(kg)		6.3
	VESA 壁掛		400 x 200
	邊框寬度(mm)		7.9 (Side), 9.8 (Top/Bottom)
操 作	操作溫度/濕度		0°C~ 40°C / 10~80%
特殊功能	特殊功能	H/W	Temperature Sensor, Portrait Installation support, Clock Battery(168hrs Clock Keeping),Video Wall Daisy Chain(HDCP2.2:4EA,HDCP1.4:7EA), Shock and Vibration certificated(IEC 61373), WiFi Module Embedded
		S/W	Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option, Plug&Play (Initial Setting)
內部媒體播放器	嵌入式		Yes
	作業系統		Tizen 4.0 (VDLinux)
	SSSP		MagicInfo Player S6, SSSP 6.0

01 LCD Signage

小型顯示器

小巧、多用途解決方案

QBR/QBR-T 系列

特色

FHD解析度
支援1920 x 1080 FHD解析度，呈現清晰與易讀的內容。

觸控功能*
10點觸控與快速反應時間帶來直覺式介面。

防眩光螢幕
無論室內的光線狀況為何，都能提供更清晰的畫面。

16/7不間斷運作
確保專業用途能可靠的運作。

內嵌媒體播放器
無須任何外接媒體播放器，便能有效、無縫地播放內容。

纖薄、聰明的設計
無論壁掛與直立，都能在狹小的空間裡，將空間利用最大化。

中央IR、內建Wi-Fi
即使是訂製安裝，也能輕鬆方便地進行遠端操控。

Knox安全系統
透過嚴密的3層安全平台限制內容存取與硬體。

*觸控功能僅限QBR-T系列。

規格表

型　號			QB13R	QB13R-T
面 板	對角線尺寸		13	13
	解析度		1920 x 1080	1920 x 1080
	亮度(典型值)		300	250
	對比度		800:1	600:1
	可視角度(水平/垂直)		178/178	178/178
	反應時間		8ms(Typ.)	8ms(Typ.)
	使用小時		16/7	16/7
	霧度Haze(%)		10%	10%
聲 音	喇叭類型		Built in Speaker(5W)	Built in Speaker(5W)
連結性	輸 入	RGB	N/A	N/A
		VIDEO	HDMI 1.4 (1)	HDMI 1.4 (1)
		HDCP	HDCP 2.2	HDCP 2.2
		AUDIO	N/A	N/A
		USB	USB 2.0 x 1	USB 2.0 x 1
	輸 出	RGB	N/A	N/A
		VIDEO	N/A	N/A
		AUDIO	Stereo Mini Jack	Stereo Mini Jack
		Power Out	N/A	Power Out - N/A / Touch Out - x1
	外部控制		RS232C(in) thru stereo jack, RJ45	RS232C(in) thru stereo jack, RJ45
	外部感測器		N/A	N/A
電 源	電源供應		AC100 - 240 V~ (+/- 10 %), 50/60 Hz	AC100 - 240 V~ (+/- 10 %), 50/60 Hz
	耗電量	最大值	27.5	27.5
		平均值	13	14
		睡眠模式	0.5	0.5
機械規格	機身尺寸(mm)		322.0x193.5x28.2	322.0x193.5x29.8
	機身重量(kg)		0.9	1.1
	VESA 壁掛		100 x 100	100 x 100
	邊框寬度(mm)		12.2	13.1
操 作	操作溫度/濕度		0°C~ 40°C / 10~80%	0°C~ 40°C / 10~80%
特殊功能	特殊功能	H/W	Temperature Sensor,Pivot Display, Clock Battery(168hrs Clock Keeping), Built in Speaker(5W 1ch), IP5x Rating, Wi-Fi	Temperature Sensor,Pivot Display, Clock Battery(168hrs Clock Keeping), Built in Speaker(5W 1ch), IP5x Rating, Wi-Fi, 10 Point Touch(Max)
		S/W	Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option, Plug&Play (Initial Setting)	
內部媒體播放器	嵌入式		Yes	Yes
	作業系統		Tizen 4.0 (VDLinux)	Tizen 4.0 (VDLinux)
	SSSP		MagicInfo S6, SSSP 6.0	MagicInfo S6, SSSP 6.0