

Summary : The world's leading AIoT intelligent ecology commercial LED display with poster screen

N181P-83 is the AIoT intelligent ecology commercial LED display with poster screen, integrating the globally leading LED fine pitch technology and intelligent Android System , widely used at the airport, train station, supermarket and shopping mall, retail chains and so on

Functions

- Global ultra-thin design(43mm) , over 97% color saturation , exquisite picture quality , low brightness and high gray , 8-level freely adjustable brightness .
- Adopt Android system, very expandable ;
- Support USB 、 HDMI Sync 、 Lan AAP control to play , Support WIFI 、 Ethernet internet connection and so on
- Support Sync/async model switch to play, support multiple splicing large screen to meet more advertisements and events
- Support intelligent cluster management & control , support remote centralize management, auditing, play and control. It is the precision marketing tool that multiply the advertising value.
- Support remote intelligent monitoring and timing switch ; support Android cellphone and smart end to remote wireless interacting operate in anytime and anywhere, totally controlled.
- Support digital Dolby 5.1 channel audio output. Audio-video brings a better audience experience
- Support standing, wall mounted, hanging and creative DIY as horizontal and vertical installation.
- Plug and play , Any video automatically plays full screen , zero setting , quick and simple ;
- User-lever front maintenance , all-weather protection technology, anti-broken LED, moisture-proof, anti-static, radiation-proof, wear-resisting and high-efficiency heat dissipation.



Support multiple installations



Specification

Product Type	N181P-83
Operation System	NOVA Star OR Android
Screen Size	83 inches
Resolution	320*1080
Viewing Area	600mm×2025 mm
Brightness	480-800cd/m ² (8 level adjustable)
Contrast Ration	4000:1
Gray Scale	14bit
Refresh Rate	3840Hz
Viewing Angle	160°(H) / 160°(V)
Response Time	≤0.5ms (Typ)
Video Interface	HDMIx2 (1in1out) , USB 2.0x2
Audio Interface	External Audio x 1 interface
Control Interface	RJ45x1、USB-Bx1、WIFI、
Input Voltage	100-240V~50/60Hz
Power Consumption	≤245W (Average) / ≤820 W (peak)
Overall Dimension	630.21mm*2060.58mm*80.1mm(42.6mm)
Installation	Base/Standing/Hanging/Wall mounted (optional)
Storage Temperature	-20°C ~ 60°C
Working Temperature	-10°C ~ 40°C
Working Humidity	10% ~ 60%RH
Life Span	≥100000Hours
Accessories	Tool、Spare parts、HDMI wire、Specification

因配置環境與使用需求不同，參數或有變化，最終解釋權由諾亞媒體股份有限公司所有。



NOVA MEDIA 官網

諾亞媒體股份有限公司



A 105台北市松山區南京東路四段1號7樓

T 02-2718-2099 統編:28469434

NOVA MEDIA CO.,LTD 7F, No.1, Sec.4, Nangjing S.Rd., Taipei, Taiwan

產品諮詢專線: 02-2718-2099 轉150

Structural Chart (Unit mm)



美觀包邊設計
屏體間鷹勾鎖彼此扣緊



支援最多6片拼接
亦可快速搬移展示



真空吸電動工具
模組正面拆卸維修

